

Scattering of second sound waves by quantum vorticity.

Fernando Lund*and Victor Steinberg[†]
Laboratoire de Physique, ENS de Lyon
46 Allée d'Italie, 69364 Lyon, France

Abstract A new method of detection and measurement of quantum vorticity by scattering second sound off quantized vortices in superfluid Helium is suggested. Theoretical calculations of the relative amplitude of the scattered second sound waves from a single quantum vortex, a vortex ring, and bulk vorticity are presented. The relevant estimates show that an experimental verification of the method is feasible. Moreover, it can even be used for the detection of a single quantum vortex.

PACS Numbers: 43.20.+g, 47.37.+q, 67.40.Pm, 67.40.Vs

*Permanent address: Departamento de Física, Universidad de Chile, Casilla 487-3, Santiago, Chile

[†]Permanent address: Department of Physics, Weizmann Institute of Science, Rehovot, 76100, Israel

Quantum vorticity in a superfluid, its properties, nucleation and dynamics, has been an important and long standing subject in a quantum fluid physics for several decades[1]. The main experimental tool from the very beginning to investigate quantum vorticity has been second sound[2]. Ever since the first experiments by Vinen[3] the only method which has been used in this respect, is the measurement of the variation and anisotropy of second sound attenuation due to the presence of quantum vorticity[4]. This has turned out to be a very useful and powerful tool. However, the fact that second sound is a radiative hydrodynamic mode suggests alternative methods to probe quantum vorticity, by analogy with the methods that have been developed in classical hydrodynamics in recent years. One of them is to measure the phase difference of a dislocated, or splitted, wave front, a phenomenon that is analogous to the Aharonov-Bohm effect[5]. This method has been used to probe a bathtub vortex with water surface waves[6]. It was also used recently to measure the quantized vorticity of a single vortex in superfluid helium[7]. Another approach, which is the topic of this Letter, is to measure scattering of sound waves by vorticity[8]. This method was successfully used recently to measure vorticity in the vortex array of the Karman street generated by flow past a cylinder at low Reynolds number[9]. In this Letter we present calculations and numerical estimates for the scattering of second sound waves due to quantum vorticity. Calculations are valid for any number of vortices both in two and three dimensions, and in three they may be of arbitrary shape. The estimates convincingly show that the method discussed is very sensitive and allows for the detection of a single quantum vortex. This method has the advantages of being practically unperturbative and fast, so it can be used as a powerful probe to study nucleation of quantum vortices or vortex rings in superfluid helium.

A single, straight, isolated quantum vortex consists of a core of radius a , outside of which the flow is potential, with the velocity of the superfluid component given by

$$v_s = \nabla\phi$$

where $\phi = \Gamma\theta/2\pi$, with θ the polar angle around the point vortex, and $\Gamma = h/m$ the quantum of circulation. It is important to note that this velocity potential is multivalued. At this level the normal flow is insignificant. Next, a second sound wave is sent onto this vortex. The wave motion will induce an oscillatory motion of the vortex core which will in turn radiate second sound. This is the basic mechanism for the scattering of second sound by a quantum vortex. The scattering of first sound by a quantum vortex in two dimensions was calculated by Pitaevski[10] in a Born approximation, and by Fetter[11] in an exact form. Both used a hydrodynamic approximation. This issue has been recently readdressed within the framework of a many body wave function description of elementary

excitations in [12].

In order to obtain a first approximation to this problem from a formal point of view, it is best to fix one's attention upon a potential velocity field, soon to be identified with the superfluid velocity, $v_s = \nabla\phi$, whose scalar potential ϕ obeys

$$\frac{\partial^2\phi}{\partial t^2} - c_2^2\nabla^2\phi = 0 \quad (1)$$

with c_2 the speed of (second) sound waves, for time scales such that viscous and thermal conduction effects can be neglected. Vortices are accounted for by multivalued velocity potentials ϕ : in two dimensions, a polar angle centered at $\vec{x}_0$ gives a point vortex in that location; in three dimensions the solid angle subtended at a given point by a closed curve gives a vortex loop along that curve. Nonlinear terms can also be neglected when the second sound frequency is large compared to the time scale for vortex flow on a length scale comparable to wavelength λ . Also if $\lambda \gg a$, the vortex can be considered as a point in two dimensions, or as a filament in three. The problem of finding the second sound generated by a vortex filament undergoing prescribed motion is thus reduced to finding the appropriate multivalued solutions of Eqn. (1). The necessary theoretical framework to handle such problems has been developed by one of us[13] in the context of classical hydrodynamics, and the relevant formulae can be simply translated. The main result to be used is that the radial component of the far field velocity, v_s^r , generated by a vortex filament parametrized by $\vec{X}(\sigma, t)$, where σ is a Lagrangean parameter labeling points along the filament:

$$v_s^r(\vec{r}, t) = \frac{\Gamma\epsilon_{ijk}\hat{r}_i}{4\pi c_2^2|\vec{r}|} \frac{\partial}{\partial t} \oint d\sigma \dot{X}_j X'_k \quad (2)$$

where an overdot means time derivative, a prime means derivative with respect to σ and the right-hand-side is supposed to be evaluated at the retarded time $t_{\text{ret}} = t - |\vec{r}|/c_2$. If a plane wave of amplitude $\vec{v}_s^0$, wave vector $\vec{k}_0$ and angular frequency ν_0 is incident upon this filament, it will oscillate with a velocity that is proportional to the local flow velocity[14]:

$$\dot{X}_i = C_{ij}v_{sj}^0 e^{i(\vec{k}_0 \cdot \vec{X} - \nu_0 t)}. \quad (3)$$

and the determination of the coefficients C_{ij} will be the subject of subsequent computation.

Whenever many vortex filaments are present and their mean separation is small by comparison with the sound wavelength they can be described in terms

of a continuous vorticity distribution $\vec{\omega}(\vec{y}, t)$ through the substitutions

$$\begin{aligned} \Gamma \oint d\sigma X'_j &\longrightarrow \int d^3y \omega_j(\vec{y}, t) \\ \vec{x} &\longrightarrow \vec{y}. \end{aligned} \quad (4)$$

Using this, and substituting (3) into (2) leads to the following approximate expression for the amplitude ratio $\tilde{A}$ of wave scattered into frequency ν to incident wave:

$$A \equiv \frac{v_s^r(\vec{r}, \nu)}{v_s^0} \sim \frac{ie^{i\nu|\vec{r}|/c_2}\nu\pi^2}{c_2^2|\vec{r}|} \epsilon_{jik} \hat{r}_i \hat{k}_{0m} C_{jm} \tilde{\omega}_k(\vec{q}, \Delta\nu), \quad (5)$$

where θ is the scattering angle, a tilde denotes Fourier transform in space and time, $\vec{q} = (\nu\hat{r}/c_2 - \vec{k}_0)$ is the momentum transfer, $\Delta\nu = \nu - \nu_0$ is the frequency shift and

$$C_{jm} = (1 - \frac{B'}{2})\delta_{jm} - \frac{B}{2}\epsilon_{jpm}\hat{\omega}_p.$$

Now, there are three important points that must be dealt with in order to turn the approximate expression (5) into an exact one: The first is that the oscillatory vortex motion will generate not only second, but also first sound. The second is that second sound does not obey Eqn. (1), and the third is that, in addition to the local interaction between sound and vorticity just considered, there will be a nonlocal interaction due to the nonlinear coupling between the sound and vortical motions[15], as well as additional effects due to mutual friction.

In order to deal with the first point note that first sound will be radiated at wavelengths $\sim c_1/\nu$ and that, as a consequence the ratio of energy radiated into first sound waves to that radiated into second sound waves is of order c_2^2/c_1^2 . We now choose to consider a situation near the lambda point, where this ratio is very small and we can neglect the first-to-second sound scattering.

The second point is that second sound obeys the equation

$$\frac{\partial^2 \vec{w}}{\partial t^2} - c_2^2 \nabla^2 \vec{w} = 0, \quad (6)$$

where $\vec{w} = \vec{v}_n - \vec{v}_s$ is the difference between the normal and superfluid velocities. However, in a scattering problem we wish to compare asymptotic states that are plane waves (globally for the incident wave, locally for the scattered wave), for which the relation

$$\vec{v}_n = -\frac{\rho_{s0}}{\rho_{n0}} \vec{v}_s$$

holds. Here ρ_{s0} (resp. ρ_{n0}) is the undisturbed superfluid (resp. normal) density. Since we have already agreed to be very near the lambda point,

$$v_n \ll v_s \quad (7)$$

and the superfluid velocity obeys the wave equation (1). Consequently, the amplitude $\tilde{A}$ given by (5) really gives the amplitude of second sound scattered by quantum vorticity, at least as far as the local interaction is concerned.

Since temperature fluctuations are linearly related to superfluid velocity for a second sound wave, $\tilde{A}$ will also give the ratio of incident to scattered temperature amplitudes. For the situation we have in mind, $c_2 \approx 10^3$ cm/sec. One requirement that must be met in order for (5) to be valid is that the frequency of the incident wave must be high compared to the time scales of vortex flow on the length scale of the wavelength of the sound. Working in the 1-100 KHz range gives wavelengths in the $1 - 10^{-2}$ cm range, for which superflow velocities evolve in the 10^{-3} - 10^{-1} s range, so this requirement is amply met.

The computation of the scattering of first sound is entirely analogous, it suffices to replace c_2 by c_1 , the speed of first sound, in (5). This means that near the lambda point the scattered second sound can easily be three to four orders of magnitude larger than the scattered first sound.

Dealing with the third point noted above, nonlocal interaction between sound and vorticity, as well as mutual friction, is harder. The proper way to do this is to start with the full nonlinear two-fluid equations[14],

$$\frac{\partial \rho}{\partial t} + \nabla \cdot \vec{J} = 0 \quad (8)$$

$$\frac{\partial J_i}{\partial t} + \nabla_j \Pi_{ij} = 0 \quad (9)$$

$$\frac{\partial \vec{V}_s}{\partial t} + \vec{V}_s \cdot \nabla \vec{V}_s = -\nabla \mu + \vec{f} \quad (10)$$

$$\frac{\partial(\rho S)}{\partial t} + \nabla \cdot (\rho S \vec{V}_n) = 0 \quad (11)$$

with

$$\begin{aligned} \vec{J} &= \rho_s \vec{V}_s + \rho_n \vec{V}_n \\ \Pi_{ij} &= p \delta_{ij} + \rho_n V_{ni} V_{nj} + \rho_s V_{si} V_{sj} \\ d\mu &= \frac{1}{\rho} dp - S dT - \frac{\rho_n}{2\rho} dW^2 \\ \vec{f} &= -\frac{B\rho_n}{2\rho} \vec{\omega}_s \wedge (\hat{\omega}_s \wedge \vec{W}) - \frac{B'\rho_n}{2\rho} \vec{\omega}_s \wedge \vec{W} \end{aligned}$$

where ρ, p, S and T are mass density, pressure, entropy per unit mass and temperature respectively, $\vec{\omega}_s \equiv \nabla \wedge \vec{V}_s$ and $\vec{W} \equiv \vec{V}_n - \vec{V}_s$. Thermal as well as viscous diffusivity effects have been neglected assuming the sound time scale to be small

enough. Terms describing the vortex self-induction have been omitted because they do not couple to the sound wave. Cubic terms in the entropy equation have been omitted because they will not contribute in the Born approximation to be considered shortly.

The next step is to describe the flow as the sum of a fast “sound” ($\vec{v}$) and slow “vortical” ($\vec{u}$) parts:

$$\vec{V} = \vec{v} + \vec{u} \quad v \ll u.$$

That is, $\vec{v}$ describes the flow consisting of small deviations of density, temperature, entropy and pressure away from equilibrium values, around which the equations are linearized. These small deviations include both first and second sound. The vortical component $\vec{u}$ is a solution of the equations obtained by considering constant density, with vortex filaments moving under their mutual and self-induction, possible external flows and appropriate boundary conditions. The interaction between the two modes is obtained by linearizing the equations not around a static value but around the vortical solution $\vec{u}$. The result is

$$\frac{\partial^2 \rho'}{\partial t^2} - \nabla^2 p' = F_1 \quad (12)$$

$$\frac{\rho_{n0}}{\rho_{s0} S_0^2} \frac{\partial^2 S'}{\partial t^2} - \nabla^2 T' = F_2 \quad (13)$$

where F_1 and F_2 are interaction terms, quadratic in the dynamical variables, but linear both in $\vec{u}$ and in the sound variables that are described by primed quantities, with equilibrium values carrying an index “0”. This set of equations has the structure of a wave equation with source terms. If the “sources” F_1 and F_2 are discarded, the usual equations describing sound (both first and second) are obtained. The solution to Eqn. (12) can be written as

$$SOUND = SOUND_{\text{inc}} + G * F \quad (14)$$

where *SOUND* is a two-vector describing first and second sound, G is a two-by-two matrix, the Green’s function for the left-hand-side of (12), that can be found with standard Fourier techniques, and F is a two-vector with components F_1 and F_2 . $SOUND_{\text{inc}}$ is a solution of the homogeneous equation. In an experiment such as we have in mind, $SOUND_{\text{inc}}$ is a plane, pure second sound wave, the incident wave, and the asymptotic behaviour of *SOUND* for large distances gives the scattered wave. It has both first and second sound components. Near the lambda point, $c_2 \ll c_1$ and $\rho_{s0} \ll \rho_{n0}$. With these ingredients (14) can be solved in a first

Born approximation that gives for the scattered temperature in the frequency domain $T'(\vec{x}, \nu)_{\text{scatt}}$,

$$\frac{T'_{\text{scatt}}}{T'_0} = \frac{ie^{i\nu|\vec{r}|/c_2}\nu\pi^2}{c_2^2|\vec{r}|} \left(H(\theta)\epsilon_{jmn}\hat{k}_{0m}\hat{r}_n\tilde{\omega}_j - \frac{B}{2}\hat{r}_i\hat{k}_{0j}\tilde{\Omega}_{ij} \right) \quad (15)$$

where

$$H(\theta) \equiv \left(1 - \frac{B'}{2}\right) - \frac{1}{2(\cos\theta - 1)} \frac{T_0 S_0}{C\rho_{n0}} \frac{\partial\rho'_s}{\partial T'},$$

C is the heat capacity, and

$$\Omega_{ij} \equiv \frac{\omega_i\omega_j}{\omega} - \omega\delta_{ij}.$$

Eqn. (15) is our main result, for which a first approximation was provided in Eq. (5).

Taking into account the temperature dependence of the superfluid density ρ_s and of the heat capacity near T_λ [16], the last term in the right-hand side of $H(\theta)$ can be estimated to be of order 2-3 at $\tau \equiv (T_\lambda - T)/T_\lambda \approx 10^{-3}$, and to grow as $\tau^{0.37}$. This value of τ is not yet close enough to the λ point for Eqns. (8) to lose their validity.

Let us now work out a few simple examples. First, one stationary, straight, vortex filament will have vorticity given by

$$\vec{\omega}(\vec{y}, t) = \Gamma\delta^{(2)}(\vec{y})\hat{y}_3$$

whose Fourier transform is, for $q_3 = 0$, which is the only relevant situation in which the scattering plane is perpendicular to the filament,

$$\tilde{\omega}(\vec{q}, \Delta\nu) = \frac{\Gamma L}{(2\pi)^3} \delta(\Delta\nu).$$

where L is the length of the filament or, in the case of a very long filament, the portion that is illuminated by the incident sound. Substitution into (5) shows that there is no frequency shift, as was to be expected for a static target. Using (5) and the frequencies we have quoted gives a typical scattered amplitude of $10^{-5} - 10^{-7}$, the higher amplitude corresponding to the higher frequency. This means that with a superconducting bolometer having a temperature resolution of 10 nK it will be possible to detect the scattered second sound wave from a single quantum vortex if the amplitude of the incident wave is higher than 1 mK. These are certainly experimentally realizable conditions.

Consider next a circular vortex ring moving with velocity V . In general, the vorticity carried by a filamentary vortex $\vec{X}(\sigma, t)$ is given by

$$\vec{\omega}(\vec{y}, t) = \Gamma \oint \delta^{(3)}(\vec{x} - \vec{X}(\sigma, t)) \frac{\partial \vec{X}}{\partial \sigma}$$

and, in the case of a circle, a convenient parametrization is given by

$$\vec{X}(\sigma, t) = (R \cos \sigma, R \sin \sigma, Vt).$$

Take the scattering plane to be the $y_1 - y_3$ plane. In this case

$$\begin{aligned} q_1 &= \frac{\nu}{c_2} \cos \theta - k_0 \\ q_2 &= 0 \\ q_3 &= \frac{\nu}{c_2} \sin \theta \end{aligned} \tag{16}$$

so that $\tilde{\omega}_2$, the only relevant component, is given by

$$\tilde{\omega}_2 = \frac{\Gamma R}{(2\pi)^3} \delta\left(\Delta\nu - \frac{V}{c_2} \nu \sin \theta\right) \int_0^{2\pi} d\sigma \cos \sigma e^{-ik_0 R(\cos \theta - 1) \cos \sigma}.$$

A Doppler shift in frequency arises from the vortex ring steady motion at velocity V . For rings whose radii are much smaller than the wavelength, $k_0 R \ll 1$ and

$$\tilde{\omega}_2 \approx \frac{-i\Gamma k_0 R^2}{8\pi^2} (\cos \theta - 1) \delta\left(\Delta\nu - \frac{V}{c_2} \nu \sin \theta\right)$$

so that

$$A \sim 10^{-7} (k_0 R)^2,$$

which appears to be very small even at 100 KHz and for rings of radius $R \sim 10^{-4}$ cm. Suppose however that we consider N parallel vortex rings separated by a distance d , as might be the case for rings nucleating at a moving obstacle. In this case the scattering amplitude is enhanced by a factor N along directions satisfying the Bragg condition

$$d\lambda \sin \theta = n \quad n = 1, 2, \dots$$

Finally, attenuation techniques have suggested that the quantum turbulent state[17] may be characterized by an anisotropic vortex tangle with a difference in vorticity parallel and perpendicular to the direction of counterflow given approximately by[1]

$$\Delta\omega = \Gamma\alpha\Lambda$$

where α is the anisotropy coefficient and Λ the vortex line density. Since the anisotropy is of order 1 and the experimental vortex line density can be as high as 10000, the corresponding scattering amplitude can be expected to be up to four orders of magnitude higher than that of the single quantum vortex. Also, in this case it is to be expected that scattering by the normal fluid vorticity will also be an important effect.

To conclude, we have calculated the scattering of second sound by quantized vortices in superfluid Helium. Near the lambda point, this is an effect several orders of magnitude larger than first sound scattering and suggests a nonintrusive way of probing quantum vorticity.

We wish to thank S. Fauve and Y. Simon for useful discussions, and, particularly, A. Reisenegger for constructive criticism. The research of F.L. is supported in part by Fondecyt Grant 1940429 and CCE Contract CI1*-CT91-0947. V. S. would like to acknowledge the support of the US-Israeli Binational Scientific Foundation (BSF)(Grant 90-00412) and The Israel Science Foundation.

References

- [1] R. J. Donnelly, *Quantized vortices in helium II*, Cambridge U. P., 1991.
- [2] L. D. Landau and E. M. Lifshitz, *Fluid Mechanics*, Pergamon Press, London (1987).
- [3] W. F. Vinen, *Proc. Roy. Soc. A* **140**, 114 (1957).
- [4] J. Wilks, *The Properties of Liquid and Solid Helium*, Clarendon Press, Oxford (1967)
- [5] Y. Aharonov and D. Bohm, *Phys. Rev.* **115**, (1959).
- [6] M. V. Berry et. al., *Eur. J. Phys.*, **1**, 154 (1980).
- [7] H. Davidowitz and V. Steinberg, to be published; H. Dawidovitz, Ph. D. Thesis, Weizmann Institute of Science, Israel (1992).
- [8] F. Lund and C. Rojas, *Physica D* **37**, 508 (1989).
- [9] C. Baudet, S. Ciliberto and J. F. Pinton, *Phys. Rev. Lett.* **67**, 193 (1991).
- [10] L. P. Pitaevskii, *Soviet physics, JETP*, **35**, 888, (1959).
- [11] A. Fetter, *Phys. Rev.* **A136**, 1488 (1964).

- [12] E. Demircan, P. Ao and Q. Niu, “Interaction of collective excitations with vortices in superfluid systems”, preprint.
- [13] F. Lund, *Phys. Fluids A* **1**, 1521 (1989).
- [14] I. M. Khalatnikov, *Introduction to the Theory of Superfluidity*, Benjamin, N.Y., 1965.
- [15] See Ref. [8] for a discussion of this point in the framework of classical hydrodynamics.
- [16] G. Ahlers, *The Physics of Liquid and Solid Helium, Part 1*, p. 85, K. J. Benneman and J. B. Ketterson, Eds., Wiley, NY (1976).
- [17] R. J. Donnelly, *Annu. Rev. Fluid Mech.* **25**, 325 (1993); J. T. Tough, “Superfluid Turbulence”, in *Progress in Low Temperature Physics, Vol VIII*, Ed. by D. F. Brewer, North-Holland (1982).